



DECLARATION OF PERFORMANCE

No. FLORIM 001

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$
2. Intended use(s)
For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A.,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 25/06/2013

.....
Place and date of issue

.....
Signature



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE MO ITALY / T. +39 0536 840111 / F. +39 0536 844750
WWW.FLORIM.IT / INFO@FLORIM.IT / CAPITALE SOCIALE EURO 50.000.000 I.V.
ISCR. AL REG. DELLE IMPRESE DELLA C.C.I.A.A. DI MODENA / COD. FISC. E P. IVA IT 01265320364



**Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata**

No. FLORIM 001

**Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)**

Rev. 4 del/of/de/vom/de/a 03/03/2015

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka

REX

Serie / Series / Kolekcja	CENT/TS 16165:2012 Annex B α_{SHOD}	BCRA D.M. 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ABISKO	α da 6° a 10°	> 0,4	R9	N.P.D.
ALABASTRI DI REX shiny	N.P.D.	N.P.D.	N.P.D.	N.P.D.
ARDOISE matte	α da 11° a 19°	> 0,4	R10	N.P.D.
ARDOISE grip	α da 20° a 27°	> 0,4	R11	Classe 2
CHATEAUX DE LA LOIRE	α da 11° a 19°	> 0,4	R10	N.P.D.
CONCREATE	N.P.D.	N.P.D.	N.P.D.	N.P.D.
CREMA MARFIL SELECT naturale	α da 6° a 10°	N.P.D.	R9	N.P.D.
CREMA MARFIL SELECT lucido	N.P.D.	> 0,4	N.P.D.	N.P.D.
FRAMES	N.P.D.	> 0,4	R9	N.P.D.
I GIOIELLI DI REX (pavimento)	N.P.D.	N.P.D.	N.P.D.	N.P.D.
HORN	α da 6° a 10°	N.P.D.	R9	N.P.D.
GALUCHAT	N.P.D.	N.P.D.	R9	N.P.D.
GLAMWOOD	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I BIANCHI DI REX matte	α da 6° a 10°	> 0,4	R9	N.P.D.
I BIANCHI DI REX shiny	N.P.D.	> 0,4	N.P.D.	N.P.D.
I MARMI DI REX shiny	N.P.D.	> 0,4	N.P.D.	N.P.D.
I MARMI DI REX matte	α da 6° a 10°	> 0,4	R9	N.P.D.
LA ROCHE strutturato	α da 20° a 27°	> 0,4	R11	Classe 2
LA ROCHE smooth	α da 6° a 10°	> 0,4	R9	N.P.D.
LA ROCHE anticato naturale	α da 11° a 19°	> 0,4	R10	Classe 1
LEAVES	α da 6° a 10°	> 0,4	R9	N.P.D.
LE CASCINE	N.P.D.	> 0,4	N.P.D.	N.P.D.
LE ESSENZE DI REX matte	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LE ESSENZE DI REX shiny	N.P.D.	N.P.D.	N.P.D.	N.P.D.
LOGICA	N.P.D.	> 0,4	N.P.D.	N.P.D.
LOGICA GRAFFIATO	α da 20° a 27°	> 0,4	R11	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE MO ITALY / T. +39 0536 840111 / F. +39 0536 844750
WWW.FLORIM.IT / INFO@FLORIM.IT / CAPITALE SOCIALE EURO 50.000.000 I.V.
ISCR. AL REG. DELLE IMPRESE DELLA C.C.I.A.A. DI MODENA / COD. FISC. E P. IVA IT 01265320364

MAGISTRA ASPER	α da 11° a 19°	> 0,4	R10	N.P.D.
MAGISTRA PICTUM	N.P.D.	> 0,4	N.P.D.	N.P.D.
MATERRE	N.P.D.	> 0,4	R9	N.P.D.
MATOUCHE	N.P.D.	> 0,4	N.P.D.	N.P.D.
MATOUCHE – Croco	N.P.D.	N.P.D.	N.P.D.	N.P.D.
METAUX	N.P.D.	> 0,4	R9	N.P.D.
METROWALL	N.P.D.	N.P.D.	N.P.D.	N.P.D.
PIERRES matte	α da 6° a 10°	> 0,4	R9	N.P.D.
PIERRES shiny	α da 6° a 10°	N.P.D.	R9	N.P.D.
PIERRES STRUTTURATA	α da 20° a 27°	> 0,4	R11	N.P.D.
PIETRA DEL NORD SOFT	N.P.D.	> 0,4	N.P.D.	N.P.D.
PIETRA DEL NORD naturale anticato	α da 11° a 19°	> 0,4	R10	N.P.D.
PIETRA DEL NORD grip	α da 20° a 27°	> 0,4	R11	Classe 2
PILLARGURI	N.P.D.	> 0,4	R9	N.P.D.
ROSA DEL DESERTO	α da 11° a 19°	> 0,4	R10	N.P.D.
SELECTION OAK	α da 6° a 10°	> 0,4	R9	N.P.D.
SELECTION OAK STRUTTURATO	α da 20° a 27°	> 0,4	R11	N.P.D.
SHABUI	N.P.D.	> 0,4	R10	N.P.D.
SLATE SOLUTIONS	N.P.D.	> 0,4	R9	N.P.D.
STRIPES	N.P.D.	N.P.D.	R9	N.P.D.
TAIGA matte	α da 6° a 10°	N.P.D.	R 9	N.P.D.
TAIGA GRIP	α da 20° a 27°	> 0,4	R11	N.P.D.
TOUCH STONE	N.P.D.	N.P.D.	N.P.D.	N.P.D.
UNIQUE grip	α da 20° a 27°	> 0,4	R11	N.P.D.
UNIQUE matte	α da 6° a 10°	> 0,4	R 9	N.P.D.
VISIONS GLOSSY	N.P.D.	N.P.D.	N.P.D.	N.P.D.
VISIONS SOFT	α da 6° a 10°	> 0,4	R9	N.P.D.
VISIONS WOOD	α da 11° a 19°	> 0,4	R10	N.P.D.
VISIONS GRIP	α da 20° a 27°	> 0,4	R11	N.P.D.

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05	
FLORIM 001	
EN 14411:2012	
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass