

# PRODUCT SPECIFICATION SHEET




THE ULTIMATE  
FLOORING EXPERIENCE

## Footnotes™ FiberFloor® Sheet Flooring

### PRODUCT SPECIFICATIONS

<b>Series:</b>	58000
<b>Wearlayer:</b>	Urethane Topcoat / PVC Wearlayer (Low Gloss)
<b>Nominal Wearlayer Thickness:</b>	.020" (0.50 mm)
<b>Nominal Total Thickness:</b>	.085" (2.15 mm)
<b>Widths:</b>	6' (1.8m) and 12' (3.6m)
<b>Maximum Roll Size:</b>	6' – 68 (56 m <sup>2</sup> ) 12' – 135 (112 m <sup>2</sup> )
<b>Weight per Sq. Yd. (Lbs):</b>	3.65 (1.66 kg)
<b>ASTM F-970 Static Load Limit:</b>	250 lbs/in <sup>2</sup> (113 kg)
<b>ASTM F 1303:</b>	Type I, Grade 1, Class C
<b>ASTM E-648 Flooring Radiant Panel:</b>	Class 1
<b>HUD/FHA Minimum Property Standards:</b>	Meets Wearlayer Thickness
<b>FloorScore® Certification SCS-EC10.3-2014:</b>	SCS-FS-02746



### INSTALLATION

<b>Use:</b>	Residential
<b>Installation System:</b>	Glueless or Full Spread.
<b>Location:</b>	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
<b>Adhesive:</b>	Tarkett QBond-One™
<b>Adhesive Application:</b>	<b>Releasable</b> - Apply adhesive evenly over substrate using a medium nap paint roller. Allow adhesive to dry until tacky to the touch. <b>Permanent</b> - Apply adhesive with a 1/32" deep x 1/16" wide x 1/32" apart notched trowel. Place flooring into adhesive immediately after application. When installing over an existing floor, allow adhesive to dry until it is tacky to the touch.
<b>Seam Method:</b>	<b>Glueless-Double-cut dry</b> , use Tarkett S875 Floating Seam Tape under seams on all approved substrates & Tarkett S860 Seam Tape over concrete. <b>Full Spread (Releasable)</b> - Double-cut. No tape required. <b>Full Spread (Permanent)</b> - Double-cut dry. Use Tarkett S860 Seam Tape.
<b>Seam Sealer:</b>	Tarkett DT-65 (Low Gloss)

- Maintain the work area, flooring and adhesive between 65° F and 85° F (18°C - 30°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Use only cementitious based patching and leveling compounds.
- Unroll flooring and allow material to relax for 10-20 minutes before fitting.
- When installing using the Glueless Installation System, leave a 1/4" space between flooring and all verticals (walls, pipes, cabinets, etc.).
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One™.
- When using the full spread application, roll flooring in both directions with a 75 lbs. (34 kg) 3-section floor roller.
- Protect sealed seams from all traffic for a minimum of 3 hours.

### CARE AND MAINTENANCE

- When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temperature between 65° F and 85° F. Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner. Dilute floor cleaner accordingly.

### LIFETIME LIMITED RESIDENTIAL WARRANTY, 10 YEAR LIMITED LIGHT COMMERCIAL

- The following categories are covered with a lifetime limited warranty when installed residentially and a 10 year limited warranty when installed in a light commercial application for as long as the original purchaser owns the flooring. Proof of purchase is required for claim submittal. Please refer to our Consumer Protection Guide on TarkettNA.com for complete information.

RESIDENTIAL		LIGHT COMMERCIAL
Wear and Manufacturing Defects	Rip, Tear, Gouge and Indent	Wear
Year Traffic/Asphalt Stain	Common Household Stain	Manufacturing Defects
Moisture Stain (Concrete only)	Underlayment panel Stain	
Scuff		