

# Venture

## Modular

### Product Specifications

Style Name	Kool
Style Number	40202
Surface Texture	Multilevel Loop
Pile Fibre Content	100% BCF Olefin-Velana
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free

	<u>Imperial</u>	<u>Metric</u>
Pile Weight	20.0 oz / s.y.	678 g/m2
Gauge	1/12 ga	47.2 / 10 cm
Stitches	10.5 / in.	41.3 / 10 cm
Pile Height	0.142 in.	3.6 mm
Pile Thickness	0.134 in.	3.4 mm
Density Factor	5373	11.70 ktex
Total Weight	111.04 oz / s.y.	3764 g/m2

### Performance Specifications

Flammability	Meets ASTM E-648 test standards Radiant Panel Class II
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Acoustique ASTM-E3133	70
Acoustique ASTM-E492	60


#### Installation Method's




Quarter-Turn



Monolithic



Brick



Ashlar

### Warranty Information

10 years Limited Commercial Wear & Anti-Static / 20 years Limited Residential Wear & Anti-Static  
10 years Limited Commercial Against Delamination / 20 years Limited Residential Against Delamination  
10 years Limited Commercial on Dimensional Stability / 20 years Limited Residential on Dimensional Stability  
10 years Limited Commercial Against Backing Deterioration / 20 years Limited Residential Against Backing Deterioration

### Environmental

Indoo air quality no. GLP 0006

### Dimension

Tile (PermaFuse)	19.68" x 19.68"	50 cm x 50 cm
------------------	-----------------	---------------

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice