



L.A. LIGHTS

`		
PRODUCT SPECIFICATIONS:		
COLLECTION NAME :	Modulor	
STYLE NUMER :	20002	
PRODUCT TYPE :	Carpet Tile	
SURFACE TEXTURE :	Level Loop	
PILE FIBER CONTENT:	100% BCF Anti-Static Colorloc™ Nylon	
DYE METHOD:	Solution Dyed	
PRIMARY BACKING:	Non-Woven Polyester	
SECONDARY BACKING:	PermaFuse™ Technology - Fiberglass Reinforced Thermoplastic	
	IMPERIAL	METRIC
PILE WEIGHT (AT TUFTING) :	19.0 oz per s.y.	644 g/m²
GAUGE:	5/64 ga	50 / 10 cm
STITCHES:	9.0 per inch	35.5 / 10 cm
PILE HEIGHT:	0.157"	4.0 mm
PILE THICKNESS :	0.110"	2.8 mm
DENSITY FACTOR:	6218	10.4 ktex
WIDTH:	19,68" x 19,68"	50 cm x 50 cm
TOTAL WEIGHT:	133.96 oz / s.y.	4541 g/m²
PERFORMANCE SPECIFICATIONS:		
FLAMMABILITY:	Meets ASTM E-648 test standards Radiant Panel Class I	
SMOKE DENSITY:	Meets ASTM E-662 < 450 Flaming Mode	
ANTI-STATIC PROPERTIES :	Less than 3.0 kv at 20% R.H. & 21°C	
LIGHTFASTNESS:	L5 or Better	
RESISTANCE TO WET CLEANING:	Grey Scale 5	
RECOMMENDED INSTALLATION METHOD(S):	Quarter-Turn ↑→ ↑	
DIMENSIONAL STABILITY:	Less than 0.05%	
WARRANTIES:		
	Limited Lifetime Commercial Wear & Anti-Static	
	Limited Lifetime Against Delamination	
	Limited Lifetime on Dimensional Stability	
	Limited Lifetime Against Backing Deterioration	
ENVIRONMENTAL:		
INDOOR AIR QUALITY NO.:	Green Label Plus : ID # GLP 3315	
RECYCLED CONTENT:	40% of Total Weight	

Venture Carpets Inc. reserves the right to modify the specification to improve this product without prior notice and without prejudice. Colorloc™, PermaFuse™ are registered trademarks of Venture Carpets. Shade and backing may vary from sample. For complete warranty information, go to www.venturecarpets.com