

LEAF LUXURY VINYL FLOORING

TECHNICAL SPECIFICATIONS

| | Metric | Imperial |
|---|---|----------|
| Gauge | 2.00 mm | 0.079" |
| Dimensions <ul style="list-style-type: none"> Planks | 152 mm x 1219 mm | 6" x 48" |
| Wear Layer Thickness | 0.3 mm (0.012") | |
| ASTM E 648 – Critical Radiant Flux CRF (W/cm ²) | > 0.45 | |
| ASTM E 662 – Smoke Density | ≤ 450 | |
| ASTM F 925 – Chemical Resistance | Meets requirements – (details upon request) | |
| ASTM F 970 – Static Load (modified @ 2,500 psi) | ≤ 0.005" | |
| ASTM F 1700 – Solid Vinyl Floor Tile | Class III, Type A or B | |
| ASTM F 1914 – Residual Indentation | ≤ 8% | |
| ASTM F 2055 – Squareness | 0.010" maximum | |
| Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's) | FloorScore Certified by SCS Certification Registration Number SCS-FS-03325 | |
| Maintenance | Very low | |
| PU (Polyurethane) surface treatment | Facilitates maintenance | |
| Adhesives: PS-30 AD-535 | Regular traffic Heavy traffic/rolling loads | |
| Limited Wear Warranty | 10 years | |

Please note that technical web site documents prevail.

