-----

REVISION DATE: 02-21-2011 SUPERSEDES: None

# SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street

Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT NUMBER: POWER GROUT 945 LIGHT BUFF

PRODUCT DESCRIPTION: Cement PRODUCT IDENTIFIER: 829043PM

# **SECTION 2: HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW** 

PHYSICAL STATE: Solid

COLOR: Opaque Tan ODOR: Odorless

Severe eye irritant.

Causes severe skin irritation.

Moderate respiratory tract irritant.

Harmful if swallowed.

Cancer hazard.

## POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excessive blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.

SKIN: Contact causes severe skin irritation and possible burns.

INHALATION: Can cause moderate respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to crystalline silica may cause silicosis.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Severely irritating to mouth, throat, and stomach.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs

# REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

Titanium dioxide

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT
---------------	------	---------

Crystalline silica	14808-60-7	50 - 70	
Alumina cement	65997-16-2	10 - 30	
Calcium sulfate, hemihydrate	26499-65-0	5 - 10	
Calcium carbonate	471-34-1	1 - 5	
Portland cement	65997-15-1	1 - 5	
Titanium dioxide	13463-67-7	1 - 5	

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

# **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.

IF VAPORS INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

## **SECTION 5: FIRE FIGHTING MEASURES**

FLASH POINT:

AUTOIGNITION TEMPERATURE:

LOWER EXPLOSIVE LIMIT (% in air):

UPPER EXPLOSIVE LIMIT (% in air):

Not established

Not established

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: There is a possibility of pressure buildup in closed containers

when heated. Water spray may be used to cool the containers.

Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

## SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be severely irritating or toxic. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, and the area in which the spill occurred. Never exceed any occupational exposure limits.

CLEAN-UP: Avoid creating dusts. Cover material with absorbent and moisten and collect

for disposal.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

## **SECTION 7: HANDLING AND STORAGE**

Handling: Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use

only in a well ventilated area. Avoid breathing material.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Prevent contact with this product. Wear chemically resistant gloves,

long sleeved shirt, an apron, and other protective equipment

depending on conditions of use.

GLOVES: Butyl rubber

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved

air purifying respirator with dust/mist filter.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

#### **EXPOSURE LIMITS:**

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL	
Crystalline silica	0.025 mg/m3 TWA (respirable fraction)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))	
Alumina cement	Not established	Not established	
Calcium sulfate, hemihydrate	Not established	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	
Calcium carbonate	Not established	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	
Portland cement	1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA (total dust)	

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: Solid
COLOR: Opaque Tan
ODOR: Odorless
ODOR THRESHOLD: Not established

WEIGHT PER GALLON (lbs.): 11.00

SPECIFIC GRAVITY: 1.31 SOLIDS (% by weight): 100.0

Not applicable

Not established FLASH POINT: Non flammable Not established BOILING POINT (deg. C): FREEZING/MELTING POINT (deg. C): Not established VAPOR PRESSURE (mm Hg): Not established VAPOR DENSITY: Not established **EVAPORATION RATE:** Not established OCTANOL/WATER COEFFICIENT: Not established VOC, weight percent Not determined

## **SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

## **SECTION 11: TOXICOLOGICAL INFORMATION**

COMPONENT	LD50/LC50
Crystalline silica	Not established
Alumina cement	Not established
Calcium sulfate, hemihydrate	Not established
Calcium carbonate	Oral LD50 Rat = 6450 mg/kg
Portland cement	Not established
Titanium dioxide	Not established

TOXICOLOGY SUMMARY: No additional health information available.

# **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

# **SECTION 14: TRANSPORTATION INFORMATION**

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED IATA: NOT REGULATED

# **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

\_\_\_\_\_

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from

DSL requirements.

EUROPEAN EINECS: As a result of the introduction of REACH into Europe, this product cannot be

imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

#### FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name CAS# %

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A D2B

## STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	50 - 70
Nickel (Carcinogen)		0.01 - 0.1
Acetaldehyde (Carcinogen)	75-07-0	0.001 - 0.01
Nickel (metallic) (Carcinogen)	7440-02-0	< 10 ppm
Lithium carbonate (Developmental toxin)	554-13-2	0.01 - 0.1

# **SECTION 16: ADDITIONAL INFORMATION**

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 3 FLAMMABILITY -- 1 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of

the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.