

## SPECIFICATION SHEET

Vendor: CHANGZHOU XINOU PLASTIC CO., LTD

Buyer: Centura Toronto

Product: Luxury Vinyl Plank&Tile

Specification: 152.4×1219.2×2mm×0.15mm, 304.8×609.6×2mm×0.15mm

ITEM	DRY BACK LVT
Test condition	Temp. 23℃ ± 2℃ Humi. 50% ± 5%
Visual Defect (shade, emboss, gloss variation, contamination, foreign materia	Observing from 60cm distance and different direction, no obviously visual defect
Registration	± 2mm
Layer thickness	Wear layer ± 0.05mm Middle/backing layer ± 0.15mm
Coating	Quantity 10g-12g/m <sup>2</sup> Anti-scratch > 2kg BS3900
Total thickness	± 0.15mm
Size	L < 400mm (± 0.3mm) L > 400mm (± 0.5mm)
Squareness straightness	< 0.25 mm
Curling after aging	< 1mm (normally 0.2mm-0.4mm)
Low temp. curling	< 1mm (normally 0.2mm-0.4mm)
Delamination test	> 1.2kgf/cm
Flexibility	40mm
Dimensional stability (80℃/6Hr)	< 0.15% (Normally W < 0.1%, L < 0.1%)
Mass per unit area g/m	± 10%
Chemical resistance	Class o EN423
Abrasion test	Class T EN660-2
Residual indentation	< 0.1mm
Toxicity	DEHP content < 800PPM Heavy metal content must comply with requirement of EN71 prt3
Color fastness	≥ 6 EN20 105 B20
Flammability resistance	Bf1-s1
Slip resistance	R9 BIA Ramp Test