

**DESCRIPTION**

Family	SARLON SURESTEP	LAGUNA	SEAGRASS	STAR	STONE
Construction	Guaranteed Slip Resistant Performance. Heterogeneous commercial compact vinyl sheet flooring embedded with "Step Crystal" particles, reinforced with a glass fiber mesh and recycled content.				
Type	All over slip resistant fine particles				
Standard	Commercial Use: Exceeds ASTM F1303 Type 1, Grade 1, Class B Backing				
Total Thickness	0.080" (2,0 mm)				
Wear Layer	0.028" (0,70 mm)				
Width	6'6" (2 m)				
Length	82 L.ft (25 mL)				
Roll Coverage	60 sq.y (50 m <sup>2</sup> )				
Weight	5.3 lb/ sq.y (2,9 kg/m <sup>2</sup> )				
Surface Finish	PUR: No Wax, No Spray Buff, for the life of the product				

**PERFORMANCE**

Chemical and Stain Resistance	Very good when tested in accordance with ASTM F925
Abrasion Resistance	ASTM F510: Best / EN 660-2: Group T
Slip Resistance	Meets or exceeds the industry recommendations for flat surfaces when tested in accordance with ASTM D2047
Static Load Resistance	Exceeds ASTM F970: 850 PSI
Wheel Castor Resistance	Pass EN425: suitable for office chairs with castors
Dimensional Stability	ISO 23999: <0.1 %
Thermal Conductivity	EN12524: 0.25 W / mK Suitable for heated floors max 27°C (85°F)
Impact Insulation Class	EN ISO 717-2: ΔL=5 dB
Sound Transmission Class	NF S 31-074: L < 75 dB class B
Flame Spread and Smoke Development	Compliant with the Canadian Building Code when tested in accordance with CAN/ULC - S102.2

**ENVIRONMENTAL**

Micro-Organism Resistance	EN-ISO 846 Bacteriostat, no growth
Indoor Air Quality, VOC Emission: v4, Credit 2	Compliant with CDPH 01350 Requirements
Low Emitting Material: Credit 4, option 1	Adhesive comply with SCAQMD Rule #1168
Recycled content 50% backing: Credit 4, option 2	100% Recyclable
Plants Certifications	ISO 9001, ISO14001, OHSAS 18001
Health and Safety	Complies with REACH regulation
Warranty: Limited 5 years	Special conditions & terms, on request

