Schluter®-TROWEL

The **Schluter®-DITRA-TROWEL**, **KERDI-TROWEL**, and **DITRA-HEAT/-DITRA-XL-TROWEL** feature square-notched designs to effectively install DITRA, KERDI, DITRA-XL, DITRA-HEAT, and DITRA-HEAT-DUO, respectively.

DITRA-TROWEL features a 11/64" x 11/64" *(4.5 mm x 4.5 mm)* square notch.

KERDI-TROWEL features a 1/8" x 1/8" *(3 mm x 3 mm)* square notch.

DITRA-HEAT/-DITRA-XL-TROWEL features a 1/4" x 1/4" *(6 mm x 6 mm)* square notch.

All Schluter® Trowels are made of uncoated stainless steel, making them even more durable.



Schluter®-TROWEL		
Item No.	**Notch Size**	**$ / Unit**
KERDI		
TRL-KER	3 mm x 3 mm - **1/8" x 1/8"**	**39.34**
DITRA		
TRL-DIT	4.5 mm x 4.5 mm - **11/64" x 11/64"**	**39.34**
DITRA-HEAT/-DITRA-XL		
TRL-DHXL	6 mm x 6 mm - **1/4" x 1/4"**	**39.34**

Schluter®-DITRA-ROLLER

Schluter®-DITRA-ROLLER is used to embed DITRA and DITRA-HEAT membranes in the bond coat during installation. The lightweight DITRA-ROLLER features a 14-1/2" *(37 cm)* wide roller and a shelf for placing 50 to 75 lbs of weight (e.g., bag of thin-set mortar or grout, box of tiles, etc.). Between uses, it can be conveniently disassembled for transport and storage.



Schluter®-DITRA-ROLLER	
Item No.	**$ / Unit**
DIRO	**307.30**