



Schluter® Thin-set Mortar

Made for Schluter membranes and boards



Schluter® SET™

Premium unmodified thin-set mortar

- Approved to set tile, including porcelain tile, over Schluter boards and membranes
- Meets the requirements of ANSI A118.1T

Item No.	Color	Weight
SET50G	Grey	50 lbs - 22.7 kg
SET50W	White	50 lbs - 22.7 kg



Schluter® ALL-SET™

Specialized modified thin-set mortar

- Engineered for use both under and over all DITRA and KERDI products
- Meets the requirements of ANSI A118.4T, A118.11, and A118.15T

Item No.	Color	Weight
SETA50G	Grey	50 lbs - 22.7 kg
SETA50W	White	50 lbs - 22.7 kg



Schluter® FAST-SET™

Specialized rapid-setting thin-set mortar

- Ready to grout in 4 hours for fast-track projects
- Meets the requirements of ANSI A118.4TF, A118.11, and A118.15TF

Item No.	Color	Weight
SETF50G	Grey	50 lbs - 22.7 kg
SETF50W	White	50 lbs - 22.7 kg

SUITABLE USES

Application	Schluter SET™	Schluter ALL-SET™	Schluter FAST-SET™
DITRA® over			
Plywood/OSB	X	✓	✓
Concrete	✓	✓	✓
Gypsum	✓	✓	✓
Vinyl flooring	X	X	✓
KERDI® over			
Gypsum board	✓	✓	✓
Cement backerboard	✓	✓	✓
Fiber-cement board	✓	✓	✓
Portland cement mortar	✓	✓	✓
KERDI®-SHOWER prefabricated substrates	✓	✓	✓
TILE over DITRA® & KERDI®			
Ceramic	✓	✓	✓
Porcelain	✓	✓	✓
Natural stone (e.g., granite, marble, etc.)	✓	✓	✓
• For Schluter Systems® applications, refer to the Schluter®-DITRA®, Schluter®-DITRA-HEAT®, and Schluter®-Shower System Installation Handbooks. • For other applications, refer to TCNA Handbook for Ceramic, Glass, and Stone Tile Installation and TTMAC Specification Guide 09 30 00 Tile Installation Manual. • Not recommended for moisture-sensitive stone, resin-backed tile, or glass tile.			

✓ = Approved use X = Not recommended

COVERAGE

Membrane-to-substrate			
DITRA-TROWEL (11/64" x 11/64" 4.5 mm x 4.5 mm)		DITRA-HEAT/XL-TROWEL (1/4" x 1/4" 6 mm x 6 mm)	KERDI-TROWEL (1/8" x 1/8" 3 mm x 3 mm)
150 ft² (13.9 m²)		100 ft² (9.3 m²)	200 ft² (18.6 m²)
Tile-to-membrane			
Trowel	DITRA/DITRA-HEAT	DITRA-XL	KERDI/KERDI-BOARD
1/4" x 1/4" (6 mm x 6 mm)	60 - 70 ft² (5.6 - 6.5 m²)	45 - 55 ft² (4.2 - 5.1 m²)	90 - 100 ft² (8.4 - 9.3 m²)
1/4" x 3/8" (6 mm x 9.5 mm)	40 - 50 ft² (3.7 - 4.6 m²)	35 - 45 ft² (3.3 - 4.2 m²)	55 - 65 ft² (5.1 - 6.0 m²)
1/2" x 1/2" (12.5 mm x 12.5 mm)	30 - 40 ft² (2.8 - 3.7 m²)	25 - 35 ft² (2.3 - 3.3 m²)	40 - 50 ft² (3.7 - 4.6 m²)
3/4" (19 mm)	25 - 35 ft² (2.3 - 3.3 m²)	20 - 30 ft² (1.9 - 2.8 m²)	30 - 40 ft² (2.8 - 3.7 m²)

Values are approximate