TECHNICAL SERVICE

SureShine[®] Cleaner and Polish

July 30, 2010



Description

SureShine Floor Cleaner is a neutral floor cleaner formulated for maintaining and cleaning resilient sheet and tile flooring. May also be used with laminate flooring.

Instructions Lightly Soiled Floors

Sweep or vacuum floor to remove loose dirt. Pour one cap full of SureShine Floor Cleaner into a clean bucket. Add one gallon of water to bucket. Clean floor using a damp mop. Rinsing of floor is not required.

Moderately to Severely Soiled Floors

Sweep or vacuum floor to remove loose dirt. Pour 4 – 6 ounces of SureShine Floor Cleaner into a clean bucket. Add one gallon of water to bucket. Apply the cleaning solution liberally to a portion of the floor and allow 1 – 2 minutes to soak. Scrub the area using a mop or soft bristle brush. Remove excess solution. Rinse floor with clean water and allow to dry thoroughly.

Removal of Old Wax or Floor Polish

For removal of old wax or floor polish, follow instructions for moderately to severely soiled floors. Add ½ cup of ammonia per gallon of cleaning solution.

WARNING - EYE IRRITANT. KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT

Eye Contact – Rinse with water for 15 minutes. Contact a physician. Skin Contact – Rinse with water. Inhalation – Move patient to fresh air.

Ingestion – Drink large quantity of water. Contact a physician.

High Gloss Polish

Description

SureShine High Gloss Floor Polish is an acrylic floor finish formulated to help protect and maintain the gloss level on resilient sheet and tile flooring.

Floor Preparation

Sweep or vacuum floor to remove loose dirt. Clean floor with SureShine Floor Cleaner. Allow floor to dry thoroughly.

Application Instructions

Stir polish well (do not shake). Pour polish into a shallow pan or bucket. Using a clean, damp sponge mop, cheese cloth or lambs wool applicator spread polish evenly and completely. Move applicator slowly so as not to cause air bubbles.

Note: One liberal coat is usually adequate. However, in high traffic areas a second application will provide extra protection. Allow a minimum of 30 minutes drying time between coats.

Coverage: Approximately 375 sq.ft. per quart.

Removing Floor Polish

SureShine Floor Polish is easily removed using SureShine Floor Cleaner. Follow instructions for moderately to severely soiled floors. Add ½ cup of ammonia per gallon of cleaning solution.

WARNING - EYE AND SKIN IRRITANT. KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT

Eye Contact – Rinse with water for 15 minutes. Contact a physician. Skin Contact – Rinse with water. Inhalation – Move patient to fresh

Ingestion – Drink large quantity of water. Contact a physician.

Low Gloss Polish

Description

SureShine Low Gloss polish is an acrylic floor finish formulated to help protect and maintain the gloss level on resilient sheet and tile flooring.

Floor Preparation

Sweep or vacuum floor to remove loose dirt. Clean floor with SureShine Floor Cleaner. Allow floor to dry thoroughly.

Application Instructions

Stir polish well (do not shake). Pour polish into a shallow pan or bucket. Using a clean, damp sponge mop, cheese cloth or lambs wool applicator spread polish evenly and completely. Move applicator slowly so as not to cause air bubbles.

Note: One liberal coat is usually adequate. However, in high traffic areas a second application will provide extra protection. Allow a minimum of 30 minutes drying time between coats.

Coverage: Approximately 375 sq.ft. per quart.

Removing Floor Polish

SureShine Floor Polish is easily removed using SureShine Floor Cleaner. Follow instructions for moderately to severely soiled floors. Add ½ cup of ammonia per gallon of cleaning solution.

WARNING - EYE AND SKIN IRRITANT. KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT

Eye Contact – Rinse with water for 15 minutes. Contact a physician. Skin Contact – Rinse with water. Inhalation – Move patient to fresh air.

Ingestion – Drink large quantity of water. Contact a physician.

