佛山出入境检验检疫局检验检疫综合技术中心

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告

TEST REPORT

报告编号:

25201400064

共 5 页 第 4 页 Page 4 of 5

	EN 14411:2012 Ceramic tiles – Definitio Annex K Requirements for						
条款 Clause	性能 Properties	检验方法 Test Method	要求 Requirements	检验结果 Results	判定 Verdict		
A	尺寸和表面质量 Dimensions and surface quality						
A.1	长度 Length 每块砖的平均尺寸相对于工作尺寸的 允许偏差	EN ISO 10545-2	±0.5%	+0.02%~+0.11%	Р		
	The deviation,of the average size for each tile (2 sides) from the work size		±2.0mm	+0.1mm~+0.4mm	P		
	宽度 Width 每块砖的平均尺寸相对于工作尺寸的 允许偏差 The deviation,of the average size for each tile (2 sides) from the work size	EN ISO 10545-2	±0.75mm	0~+0.2mm	P		
A.2	厚度 - Thickness						
	应声明厚度 The thickness shall be specified	18	声明厚度 Declared thickness	7.7mm	=		
	每块砖厚度的平均值相对于工作尺寸 的最大允许偏差 The permissible deviation, of the average thickness of each tile from the work size thickness	EN ISO 10545-2	±0.5mm	0~+0.1mm	P		
В	物理性能 Physical properties						
B.1	吸水率 质量分数	EN ISO 10545-3	E _b >10%	17.1%	Р		
	Water absorption Percent mass fraction		单个值不小于 9% Individual minimum 9%	16.7%~17.6%	Р		
B.2	破坏强度/N Breaking strength, in N	EN ISO 10545-4	≥600	663	Р		
В.3	断裂模数/(N/mm²) Modulus of rupture, in N/mm² 不适用于破坏强度≥ 3000N 的陶瓷砖 Not applicable to tiles with breaking strength≥ 3000N	EN ISO 10545-4	≥12	22.6	Р		
B.4	耐磨性 Abrasion resistance 用于地面的有釉砖的表面耐磨性	EN ISO 10545-7	报告耐磨级别 Report abrasion class	4級 Class 4	_		
	用于理图的有相框的表图顺着生 Resistance to surface abrasion of glazed tiles intended for use on floors		报告耐磨转数 Report cycles passed	2100	-		
B.6	抗热震性 Thermal shock resistance	EN ISO 10545-9	应通过此项测试 Pass	样品经试验,无炸裂 或裂纹 Fully resistance	Р		
B. 7	抗釉裂性: 有釉砖 Crazing resistance: glazed tiles	EN ISO 10545-11	应通过此项测试 Pass	样品经试验,无裂纹 或剥落 Fully resistance	P		

FSIQTC-T 2(1)/A

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

CERTIFICATE

Of Conformity

Certificate No:

25201400064

Applicant:

Address of Applicant:

Product:

INTERIOR WALL TILES

Type designation:

NC1400, Y1A04001, NC1401, NC1406

Technical data:

Dry-pressed ceramic tiles for interior wall finishes, with water absorption $E_b \ge 10\%$, Group BIII, 40cm \times 10cm, Flat, Glazed

多·英国 5·美国

正本

申请人 存

The submitted samples of the above product have been tested for CE marking according to the following European Directives:

(EU)No.305/2011-the Construction Products Regulation

Standard used for showing compliance with the essential requirements in the specified directive:
Standard Test report Issued by Date Issued by IQCTC of FSCIQ 25201400064

EN 14411:2012

Jan. 28, 2014

The referred test report shows that the product complies with standard recognized as giving presumption of

compliance with the essential requirements in the specified EU Directive.

After preparation of the necessary technical documentation as well as the conformity declaration the CE marking as shown below can be affixed on the product. Other relevant Directives have to be observed.

This certificate is NOT valid for: (i) uses in suspended ceilings; (ii) uses subject to requirements against accidental fall of objects on to transit areas; iii) uses subject to dangerous substances regulations; iv) uses in vehicular circulation areas.

This document is the property of inspection and quarantine comprehensive technology centre of Foshan Entry-exit Inspection & Quarantine Bureau, and it is not transferable. Only the applicant may reproduce this



YUAN FANGLI Director

Issue Date: Jan. 28, 2014 Expiration Date: Jan.27, 2015

Note: This certificate is part of the full report and should be read in conjunction with it.

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU 2/F, Building 18, Lanshi International Metal Exchange Center, Kulqyi Road, Charcheng District, Foshan, Guangdong, China (528000) TEL: 86-75-8936058 F Axis 86-753-8382/971.

佛山出入境检验检疫局检验检疫综合技术中心

INSPECTION AND QUARANTINE COMPREHENSIVE TECHNOLOGY CENTRE OF FOSHAN ENTRY-EXIT INSPECTION & QUARANTINE BUREAU

检测报告 TEST REPORT

报告编号: 25201400064

Report No:

共5页第2页 Page 2 of 5

釉面内墙砖 INTERIOR WALL TILES	名义尺寸 Nominal size (N)	40cm×10cm		
有釉砖 Glazed (GL)	工作尺寸 Work size	400mm×100mm×7.7mm		
вШ	预期用途 Intended use	室内墙面 Interior wall finishes		
NC1400	样品数量 Quantity of samples	15 块 15 Pieces		
	委托单位地址 Address of applicant			
	委托单位传真 Fax of Applicant			
委託单位自送样品 Samples selected by applicant	接样日期 Received on	02/01/2014		
EN 14411:2012 Ceramic tiles – Definitions, classification, characteristics, evaluation of conformity and marking Annex K Requirements for dry-pressed ceramic tiles of Group BIII (E _b >10%)				
样品经检验,所检验项目的检验结果符合 EN 14411:2012 标准中附录 K 的规定。 The results conform to the requirement of Annex K of standard EN 14411:2012 with respect to the test items.				
	INTERIOR WALL TILES 有釉砖 Glazed (GL) BIII NC1400 SET P 位 自送样品 Samples selected by applicant EN 14411:2012 Ceramic tiles conformity and marking Annex K Requirements for dry- 样品经检验,所检验项目的检验 The results conform to the re	INTERIOR WALL TILES 有釉砖 Glazed (GL) BIII BIII NC1400 R+B数量 Quantity of samples Address of applicant 委托单位传真 Fax of Applicant 医N 14411:2012 Ceramic tiles — Definitions, classification conformity and marking Annex K Requirements for dry-pressed ceramic tiles of Gro 样品经检验,所检验项目的检验结果符合 EN 14411:2012: The results conform to the requirement of Annex K of		

检验单位盖章 Stamp of Test Unit



检验单位联系方式 Address of Test Unit

地址:广东省佛山市禅城区製奇一路测 石(国际)金属交易中心十八座二楼 石(国际) 金属交易中心十八座一種 Address: 2/F, Building 18, Lanshi International Metal Exchange Center, Kuiqiyi Road, Chancheng District, Foshan, Guangdong, China (528000) 电话(Tel): 86-757-83827991 後真(Fax): 86-757-83827971 ※第(Fax): 86-757-83827971

部箱 (E-mail): fsiqte@163.com





	STIMS	网址 (uel): http://www.fsiqtc.com/
那明 Notes	All inspections are carried out conscients This report does not in any respect absolve the other 2、未经本实验室书面许可,不得部分复制本	without the prior written approval from the issuing laboratory.